

Sub. A

- Sub. A

pos  
Sub  
K2

pos  
Sub  
K2

4.

pan  
Subj

pan  
Subj

6.

6.

Sub X

Sub X

AA Cont.  
10. The personal warning light according to claim 4, wherein said controller is in electric communication with said light emitting diode light sources, said controller being constructed and arranged to selectively activate said light emitting diode light sources thereby producing more than two different types of visually distinct warning light signals.

11. The personal warning light according to claim 4, further comprising a circuit board being constructed and arranged to position said light emitting diode light sources.

12 12. The personal warning light according to claim 11, said culminator comprising at least one reflective section.

13. The personal warning light according to claim 12, said culminator comprising at least one transparent section.

14. The personal warning light according to claim 11, further comprising a plurality of culminator cups, each of said culminator cups being constructed and arranged for positioning proximate to one of said light emitting diode light sources.

15. The personal warning light according to claim 14, wherein said culminator cups are disposed in a linear array.

Sub 16 16. The personal warning light according to claim 4, said reflector comprising at least one mirror.

17. The personal warning light according to claim 4, wherein said controller is in electric communication with said light emitting diode light sources and said controller is constructed and arranged to selectively activate said light emitting diode light sources to produce a plurality of visually distinct warning light signals.

18. The personal warning light according to claim 4, wherein said controller is in electric communication with said light emitting diode light sources and said controller is constructed and arranged to independently illuminate said light emitting diode light sources.

B 16 19. The personal warning light according to claim 4, said light emitting diode light sources comprising light emitting diodes of at least two different colors.

Sub 20 20. The personal warning light according to claim 19, wherein said controller selectively activates said light emitting diode light sources to create at least one of a single colored light signal and at least one of a multi-colored light signal.

21. The personal warning light according to claim 4, wherein said light signal is selected from the group consisting of: A revolving light, a pulsating light, an alternating

Alb  
Conts

light, an oscillating light, a flashing light, a stroboscopic light, a modulated light, and any combination thereof.

22. The personal warning light according to claim 4, wherein more than two different types of light signals are produced simultaneously.

Sub  
P11

23. The personal warning light according to claim 4, wherein more than two different types of light signals are produced independently of each other.

24. The personal warning light according to claim 4, wherein more than two different types of light signals are produced in at least one combination.

Sub  
P12

25. The personal warning light according to claim 4, wherein said light emitting diode light sources are disposed in a single row.

F:\WPWORK\EEV\PATENT\9256-APP.712

Add 19